

Minisonic II PORTABLE



FLUIDS
LIQUIDS



PIPES UP TO
10 000 MM



MODEL
STANDARD



COMPACT

- › Lightweight (< 750g)
- › Easy handling

ROBUST

- › IP 68 ABS Housing

FUNCTIONS

- › Advanced Data logger
- › Records Indexing
- › USB records upload
- › Wake-up timer

VERSATILITY

- › All homogeneous fluids

HIGH PERFORMANCE

- › ESC powered
- › OLED display
- › Echo, gain & signal quality visualisation
- › Autonomy > 70 hours continuous use
- › On site «Zero» calibration
- › 10 flow calculation/s



TYPICAL APPLICATIONS

Potable water

Leakage measurement, pump flow control, inline flowmeter verification

Raw & waste water

Pump flow control, inline flowmeter verification

Hydraulic expertise

Installation diagnostic, claims handling

Civil engineering

Installation conformity & commissioning

Climatic engineering

Network balancing

Petroleum

One-off measurement

SEZTEC USA - An authorized distributor

Tel: +1.816.204.0808
E-mail: info@seztec.com
Web: www.seztec.com

MODEL	STANDARD
TECHNOLOGY	Transit time ultrasonic flow measurement · Continuous & two-way measurement
DEVICE TYPE	Portable
PIPE Ø	From 10 mm up to 10 000 mm
USE	Full-pipe flow rate measuring · One pipe · One chord
SENSOR COMPATIBILITY · MOUNTING	All Ultraflux probes · Mounting: / - V - N - W
PIPE MATERIAL	Large pipe material onboard database Multilayer: up to 3 homogeneous material
FLUID TYPE	Bubble free liquids · Large fluid types onboard database
VELOCITY RANGE	Up to +/- 30 m/s
INPUT / OUTPUT	1x 4-20 mA activ output 2x Logic output (Counting and/or status)
DISPLAY	Digital and graphic OLED high visibility display
SIGNAL PROCESSING	Echo Shape Control (acoustic signal optimisation)
DIAGNOSTIC	Signal echo visualisation · Gain · Quality index · Alarms
PERFORMANCE	<ul style="list-style-type: none"> > Accuracy up to 0,5% > Repeatability up to 0,1% > Linéarity up to 0,1% > Time resolution: 0,1 ns > Flow calculation: 10/s > Reynolds number calculation : Flow pattern taken into account
CONFIGURATION	User friendly - Intuitive 7 Pad keyboard
CONFIGURATION MODE	<ul style="list-style-type: none"> > Simple · Normal · Expert > Up to 30 different configurations memory
LOGGER	<ul style="list-style-type: none"> > Multi-variable data-logger · 2 Gb internal memory / Up to 33 millions of points > Record indexing (Site description / settings / values) > USB data-logger uploading > Sampling : from 1 second to 24 hours
WAKE-UP TIMER	Programmable activation for extended battery life
LANGUAGES	French - English (other : pending)
MEASUREMENT UNITS	Metric / imperial
AUTONOMY	>70 hours · More using wake-up timer
STANDARD ACCESSORIES	Shockproof case - Connection cables - Coupling gel - Mounting accessories
ELECTRICAL INFORMATION	Li-Ion internal battery · Charging cable supplied · Auxiliary power supply cable as an option
HOUSING	ABS · 740 g · 220 x 115 x 74 mm
PROTECTION	IP 68
TEMPERATURE LIMITS	USE From -20 to 50°C